

Lower costs with production level LED printing

With LED technology and increased productivity, the 3.2-meter EFI[™] VUTEk[®] GS3250Lx Proprinter will help you offer more applications while lowering operating costs.



High-definition imaging and LED technology

- Deliver high-definition POP graphics with true grayscale technology, 1,000 dpi, and multilayer white ink printing
- Extend the range of supported substrates with innovative ink curing technology
- Increase uptime and productivity while reducing maintenance with instant on/off LED lamps
- Drive down operating costs with decreased power consumption, fewer consumable parts, and less waste with consistent color output and simple operation
- Offer customers a greener printing solution

Continuous print productivity

- Take on more jobs and turn them faster with continuous print productivity with less than five seconds between boards
- Accurately align images using the precision alignment fence

Increased reliability and performance

- Maximize uptime with fewer parts, improved reliability standards, and easy troubleshooting
- Run multiple jobs at once with multi-queue functionality available at the user interface
- Integrate your EFI VUTEk system with EFI Web-to-Print and MIS/ERP solutions with native JDF connectivity

Features and benefits

- Production-level LED technology
- Eight-color plus two white and single-pass, multilayer printing
- Switchable to Fast-4[™] for high productivity
- Dual resolution: True 600 dpi (24 pL) or 1,000 dpi (12 pL) selectable
- Output up to 2,400 ft²/hr (223 m²/hr) and 60 4 ft x 8 ft (1.2 m x 2.4 m) boards per hour
- True variable drop grayscale print capability

Media/Handling

- Handles flexible and rigid substrates up to 126.5 in (3.2 m) wide and up to 2 in (5.08 cm) thick
- Multi-roll capable two 60 in (152 cm) rolls
- Optional heavy-duty unwinder (HDU)
- Optional extension table with casters

Productivity

- Fast-4: 2,400 ft² (223 m²) per hour
- Production up to 60 4 ft x 8 ft (1.2 m x 2.4 m) boards per hour
- Eight-color plus white 1,200 ft² (111.4 m²) per hour
 Production up to 32 4 ft x 8 ft (1.2 m x 2.4 m) boards per hour

Environmental considerations

- Compressed air: 110–145 psi maximum at 12 cf/m dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68 °F to 86 °F (20 °C to 30 °C)
- Humidity: 30% to 80% (non condensing)
- Machine weight: 6,700 lbs (3039 kg)
- Height: 66 in (168 cm)
- Width: 248 in (630 cm)
- Depth: 63 in (168 cm)
- Electrical: 3-Phase, 20 amps @ 200 230 volt supply or 10 amp @ 400 – 460 volt supply

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalized documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 650-357-3500 for more information.



EFI Fiery[®] proServer

- Optimized for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery XF digital front end (DFE) and printer allows back communication of audit information on every print job
- Powerful production tools, such as nesting, step and repeat, scaling, cropping, and tiling
- Advanced ICC color management for reliable color, quality output, and proofing-quality color

Genuine EFI Inks

- Supplied in 5.0-liter containers
- Expanded gamut CMYK pigments for world-class Pantone® matching
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability

Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware, and Fiery XF software
- Thirteen months of Essential coverage, with 24-business hour (three-business day) response
- Eligible for upgrade to:
- Critical: Providing 8-business hour (one-business day) response
- ProActive: Providing 16-business hour (two-business day) response

Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StorePront, DirectSmile, DocBuilder, DocBuilder Pro, DocKNet, DocStream, DSPdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery Jogo, Fiery Driven, the Fiery Doriven, the Fiery Doiro, Fiery Prints, the Fiery JobFlow, Fiery Jahk, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inktensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pecas, Pecas, Vision, PhotoXposure, PressVu, Printcafe, PrinteFite, PrintFice, PrintFice, PrintShet, PrintShet, PrintShet, PrintShet, Prints, Prints, Prints, Prints, Prints, Prints, Printer, Printer, Ving, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPres, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEk, Idey, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged